

PRIMO® L

Standard Seat with Pneumatic Suspension



TECHNICAL DATA PRIMO® L

This seat's reduced-travel pneumatic suspension, which runs on a 12 V or 24 V power source, effectively attenuates vibrations in even the tiniest cabs. It can be optimally set to the operator's weight using an ergonomically placed pushbutton, aided by an indicator.









Features • Standard O Optional

	PRIMO®
	L
Article no. fabric	
Compressor 12V	1293488
Compressor 24V	1293477
Article no. imitation leather	
Compressor 12V	1104725
Shock absorber nonadjustable	•
Suspension	
Pneumatic suspension with compressor	•
Suspension stroke 80 mm	•
1 Weight adjustment 45 - 170 kg, pneumatic	•
2 Fore/aft adjustment 210 mm	•
3 Lumbar support mechanical	•

	PRIMO®
	L
4 Adjustable backrest angle	•
5 Restraint system	•
Seat cushion width	470 mm
Operator presence switch (OPS)	•
OPTIONAL FEATURES	
6 Document box	0
7 Armrests height-adjustable	0
Fore/aft isolator*	0
8 Backrest extension	0
Seat heating	0

^{*}Fore/aft isolator not for earth-moving machinery

Measurements (installation dimensions)

